

TIGER G2



TG-T11-15

Article no.	TG-T11-15
Frequency	915 MHz
Duplex	Yes
Mod.type	FM-Modulation, narrow band
Code comb.	4.200.000.000
Radio type	Low IF topology
Output	10 mW (by 50 ohm)
Buttons	12 x 2 -step buttons
No. of batteries	1
Battery	Re-chargeable & exchangeable
Type of batteries	li-ion
Operating time with continuous	24 h
usage	2411
usage Weight	400 g /~ 0.9 lb
Weight	400 g /~ 0.9 lb
Weight Dimensions	400 g /~ 0.9 lb 76 x 210 x 37 mm /~ 3 x 8.3 x 1.5 ln
Weight Dimensions Protection	400 g /~ 0.9 lb 76 x 210 x 37 mm /~ 3 x 8.3 x 1.5 ln IP65
Weight Dimensions Protection Temperature	400 g /~ 0.9 lb 76 x 210 x 37 mm /~ 3 x 8.3 x 1.5 ln IP65 -20 to +55 °C / -4 to 131 F
Weight Dimensions Protection Temperature Safety level	400 g /~ 0.9 lb 76 x 210 x 37 mm /~ 3 x 8.3 x 1.5 ln IP65 -20 to +55 °C / -4 to 131 F SIL3, PLe
Weight Dimensions Protection Temperature Safety level Certifications	400 g /~ 0.9 lb 76 x 210 x 37 mm /~ 3 x 8.3 x 1.5 ln IP65 -20 to +55 °C / -4 to 131 F SIL3, PLe G Lloyd, FCC, IC
Weight Dimensions Protection Temperature Safety level Certifications On/off switch	400 g /~ 0.9 lb 76 x 210 x 37 mm /~ 3 x 8.3 x 1.5 ln IP65 -20 to +55 °C / -4 to 131 F SIL3, PLe G Lloyd, FCC, IC 24

The product picture above is for illustrative purposes only, actual product appearance might be slightly different